



(1) **EU-Type Examination Certificate**  
TRANSLATION

(2) Component Intended for Use in Potentially Explosive Atmospheres  
**Directive 2014/34/EU**

(3) Number of Certificate of EU-Type Examination:

**TPS 19 ATEX 103415 0002 U** Issue 02



(4) Product: **Fuel Dispenser Nozzle Types and variations (SL = Slimline):**  
ZVA SL, ZVA SL2, ZVA SL2 GR, ZVA SL3, ZVA SL3 GR, ZVA SL3 GR ORVR,  
ZVA 200 GR, ZVA 25, ZVA 25 GR, ZVA 32, ZVA LV for AdBlue®, ZVA HV for AdBlue®  
Special versions:  
RG / GBZ / VA (SS) / AF / SIC / DSA / Vi / VD / EP / TD / LT  
GRV / GRVP / GRV-WT / GRVP-WT / GRV-FA

(5) Manufacturer: ELAFLEX HIBY GmbH & Co. KG

(6) Address: Schnackenburgallee 121  
22525 Hamburg  
GERMANY

(7) This product and any acceptable variation thereto are specified in the schedule to this certificate and the documents therein referred to.

(8) TÜV SÜD Product Service as notified body No. 0123 according to article 17 of the Directive 2014/34/EU of the European Parliament and the Council of the European Union certifies that this product has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of products and protective systems intended for use in potentially explosive atmospheres, given in Annex II of the Directive.

The examination and test results are recorded in the confidential report 713384373-1.

(9) Die grundlegenden Sicherheits- und Gesundheitsanforderungen werden erfüllt durch Übereinstimmung mit:

**EN ISO 80079-36:2016    EN ISO 80079-37:2016    EN 13012:2021**

(10) The sign "U" placed behind the certificate number indicates that this certificate should not be confounded with certificates issued for equipment or protective systems. This partial certification may be used as a basis for certification of an equipment or protective systems.

(11) This EU-Type Examination Certificate relates only to the design and the construction of the specified product in accordance with Directive 2014/34/EU. Further requirements of this Directive apply to the manufacturing process and supply of this product.

(12) The marking of the component shall include the following:

 **II 1 G Ex h IIA**

and is valid for: Ta = -20°C bis +55°C (All Nozzle Variants except Low Temperature variant "LT")

Ta = -40°C bis +55°C (Low Temperature variant marked "LT")

Certification Body Explosion Protection  
Ridlerstraße 65, 80339 Munich

Munich, 26.01.2026

  
Dipl.-Ing. Ulrich Jacobs

Seite 1 / 3

EU-Baumusterprüfbescheinigungen ohne Unterschrift haben keine Gültigkeit.  
Diese EU-Baumusterprüfbescheinigungen darf nur unverändert weiterverbreitet werden.  
Auszüge oder Änderungen bedürfen der Genehmigung von TÜV SÜD Product Service GmbH  
Das Dokument wird intern unter der folgenden Nummer verwaltet: EX5A 103415 0002 Rev. 02

TÜV SÜD Product Service GmbH • Zertifizierstelle • Ridlerstraße 65 • 80339 München • Deutschland