

The new GasGuard GG40 nozzle from Elaflex has been designed for the US and Canadian markets to provide a simple and recognized solution for the Quick Connect (K15) propane filling systems.



Complete solutions with Break-Away (Pull-Away) and the UL listed LPG 16 S hoses.



ELAFLEX LPG 16 · EN 1762 · - 40°C · Ω · 25 bar · M





## GG40 FEATURES AND TECHNICAL INFORMATION

Like our range of GasGuard 1 ¾" ACME nozzles the new GG40 nozzle was designed to continue the strong reputation for reliability and user comfort.

- Designed acc. to EN 13760, UN R 67 & ISO 19825
- Low effort lever (lower than the GasGuard ACME nozzles)
- Light weight, easy to use, robust design for longer lifetime
- With safety hold-open latch and larger locking segments for secure connection
- Personal protection equipment not necessary (unless required by local codes or regulations)
- Improved flow rate up to 17 GPM, ultra low emission < 1cm<sup>3</sup>
- Low maintenance, simple to repair = low running cost
- Both latched and unlatched versions are UL approved
- 18 month manufacturer's warranty

The Elaflex "hanging hardware" set is a professional and reliable solution for dispenser and scale systems. When combined with our ARK 19.3 Pull-Away and GG40 Quick Connect nozzle, our hose assemblies provide AutoPropane users with increased user comfort and handling. The GG40 nozzle is compatible with the existing NB-GG Nozzle boot for secure storage.



**ELAFLEX PACIFIC PTY LTD** 

Unit 29/58 Box Road Taren Point, NSW, 2229 Australia

Tel. +61 2 8058 9258 info@elaflex.com.au elaflex.com.au

